

Section 1: IDENTIFICATION

1.1 PRODUCT IDENTIFIER

Product Name: PB Penetrating Catalyst (Bulk)
Product Code: 128-PB, 5-PB, 55-PB & 4-PB-DB

1.2 RECOMMENDED USE OF CHEMICAL AND RESTRICTIONS ON USE

Use: Lubricant

1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

Name/Address: The Blaster Corporation

8500 Sweet Valley Drive Valley View, Ohio 44125 - USA

Telephone Number: T (216) 901-5800

F (216) 901-5801

1.4 EMERGENCY TELEPHONE NUMBER

Emergency Telephone Number: ChemTel 800-255-3924

Date of Preparation: Feb. 3, 2016 Version #: 1.0

Section 2: HAZARD(S) IDENTIFICATION

2.1 CLASSIFICATION OF THE CHEMICAL ACCORDING TO OSHA HAZCOM 2012

Hazard class

Flammable Liquid 4
Serious Eye Irritation 2A
Carcinogenicity 2
Aspiration Hazard 1

2.2 LABEL ELEMENTS ACCORDING TO OSHA HAZCOM 2012

Hazard Pictogram:





Signal Word: Danger

Hazard Statement: Combustible liquid. Causes serious eye irritation. Suspected of

causing cancer. May be fatal if swallowed and enters airways.

Prevention: Keep away from flames and hot surfaces. – No smoking. Wash

hands thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and

understood. Wear protective gloves/protective clothing/eye


protection/face protection.

Response: If exposed or concerned: Get medical advice/attention. If in eyes:

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If swallowed: Immediately

Trade Name: PB Penetrating Catalyst (Bulk)

Revision date: 2017-12-13





call a poison center/doctor. Do NOT induce vomiting.

Storage: Store in a well-ventilated place. Keep cool. Store locked up.

Disposal: Dispose of contents and container in accordance with all local,

regional, national and international regulations.

2.3 ADDITIONAL INFORMATION

Hazards not otherwise classified: Not applicable.

1% of the mixture consists of ingredient(s) of unknown acute toxicity.

This product is a hazardous chemical as defined by NOM-018-STPS-2000.

Mexico Classification:



Blue = Health Red = Flammability Yellow = Reactivity White = Special Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 MIXTURES

Ingredient	UN#	H / F/ R / *	CAS No	Wt. %
Distillates (naturals um) budustus eta dilaht	Not eveileble	Not evelleble	C4740 47 0	45 55
Distillates (petroleum), hydrotreated light	Not available	Not available	64742-47-8	45 - 55
Solvent naphtha (petroleum), heavy				
aromatic	UN1270	Not available	64742-94-5	20 - 30
Distillates (petroleum), hydrotreated				
heavy naphthenic	Not available	Not available	64742-52-5	20 - 30
	UN1334/			
Naphthalene	UN2304	2/2/0	91-20-3	0.2 - 2.1
Dinonylphenol, ethoxylated, phosphated	Not available	Not available	39464-64-7	0.5 - 1.5

The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

Section 4: FIRST- AID MEASURES

4.1 DESCRIPTION OF THE FIRST AID MEASURE

Eye: In case of contact, immediately flush eyes with plenty of water for at

least 15 minutes. If easy to do, remove contact lenses, if worn. If

irritation persists, get medical attention.

Skin: In case of contact, immediately flush skin with plenty of water.

Remove contaminated clothing and shoes. Wash clothing before

reuse. Call a physician if irritation develops and persists.

Trade Name: PB Penetrating Catalyst (Bulk)

Revision date: 2017-12-13



^{*} Per NOM-018-STPS-2000



Inhalation: If breathing is difficult, remove to fresh air and keep at rest in a position

comfortable for breathing. Get medical advice/attention if you feel unwell.

Ingestion: If swallowed, do NOT induce vomiting unless directed to do so by

medical personnel. Never give anything by mouth to an unconscious

person. Get immediate medical advice/attention.

4.2 MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

Eye: Causes serious eye irritation. Symptoms may include discomfort or

pain, excess blinking and tear production, with marked redness and

swelling of the conjunctiva.

Skin: May cause skin irritation. Symptoms may include redness, drying,

defatting and cracking of the skin.

Inhalation: May be fatal if swallowed and enters airways. This product may be

aspirated into the lungs and cause chemical pneumonitis. May

cause stomach distress, nausea or vomiting.

Ingestion: May cause respiratory tract irritation.

4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENTS NEEDED

Note to Physicians: Symptoms may not appear immediately.

Specific Treatments: In case of accident or if you feel unwell, seek medical advice

immediately (show the label or SDS where possible).

Section 5: FIRE-FIGHTING MEASURES

5.1 EXTINGUISHING MEDIA

Suitable Extinguishing Media: Dry chemical, carbon dioxide or foam.

Unsuitable Extinguishing Media: Water may be ineffective for extinguishing fire.

5.2 SPECIAL HAZARDS ARISING FROM THE CHEMICAL

Products of Combustion: May include, and are not limited to: oxides of carbon, hydrocarbons.

5.3 SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE FIGHTERS

Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Cool closed containers exposed to fire with water. Do not use a solid water stream as it may scatter and spread fire. Containers may explode when heated.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition.

6.2 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING - UP

Methods for Containment: Contain and/or absorb spill with inert material (e.g. sand, vermiculite),

then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for Cleaning-Up: Scoop up material and place in a disposal container. Vapors may be

heavier than air and may travel along the ground to a distantignition

source and flash back. Provide ventilation.

Trade Name: PB Penetrating Catalyst (Bulk) Revision date: 2017-12-13





Section 7: HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING

Handling: Keep away from sources of ignition. - No smoking. Avoid contact

with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Use only outdoors or in a well-

ventilated area. (See section 8)

General Hygiene Advice: Launder contaminated clothing before reuse. Wash hands before

eating, drinking, or smoking.

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Storage: Keep locked up and out of reach of children. Keep container tightly

closed. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Store in dry, cool, well-ventilated area. (See section 10)

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 CONTROL PARAMETERS

Exposure Guidelines

Occupational Exposure Limits			
Ingredient	OSHA-PEL	ACGIH-TLV	
Distillates (petroleum), hydrotreated light	100 ppm	200 mg/m³	
Solvent naphtha (petroleum), heavy aromatic	Not available.	Not available.	
Distillates (petroleum), hydrotreated heavy naphthenic	5 mg/m³ (mist)	5 mg/m³ (mist)	
	10 ppm;		
Naphthalene	50 mg/m ³	10 ppm	
Dinonylphenol, ethoxylated, phosphated	Not available.	Not available.	

8.2 EXPOSURE CONTROLS

Engineering Controls: Use ventilation adequate to keep exposures (airborne levels of dust,

fume, vapor, etc.) below recommended exposure limits.

8.3 INDIVIDUAL PROTECTIVE MEASURES

Personal Protective Equipment:

Eye/Face Protection: Safety glasses with side-shields.

Skin Protection:

Hand Protection: Wear chemically resistant protective gloves.

Body Protection: Wear suitable protective clothing.

Respiratory Protection: A NIOSH approved respirator is recommended in poorly ventilated areas

or when permissible exposure limits may be exceeded. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected

respirator.

Trade Name: PB Penetrating Catalyst (Bulk) Revision date: 2017-12-13



General Health and Safety Measures:

Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices. Ensure that eyewash stations and safety showers are close to the workstation location.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Viscous / Oily.

Color: Orange.

Odor: Heavy aromatic.

Odor Threshold: Not available.

Physical State: Liquid.

pH: Not available.

Melting Point/Freezing Point: Not available.

Initial Boiling Point and Boiling Range: 177.8 °C (352 °F)

Flash Point: 65.6 °C (150 °F)

Evaporation Rate: >1 (n-butyl acetate = 1)

Flammability: Flammable.

Lower Flammability/Explosive Limit: Not available.

Upper Flammability/Explosive Limit: Not available.

Vapor Pressure: Not available.

Vapor Density: >1 (Air = 1)

Relative Density/Specific Gravity: 0.91 (Water = 1)

Solubility: Negligible.

Partition coefficient: n-octanol/water: Not available.

Auto-ignition Temperature: Not available.

Decomposition Temperature: Not available.

Viscosity: Not available.

Oxidizing Properties: Not available.

Explosive Properties: Not available.

VOC content: < 50%

Section 10: STABILITY AND REACTIVITY

10.1 REACTIVITY

No dangerous reaction known under conditions of normal use.

10.2 CHEMICAL STABILITY

Stable under normal storage conditions.

Trade Name: PB Penetrating Catalyst (Bulk) Revision date: 2017-12-13





10.3 POSSIBILITY OF HAZARDOUS REACTIONS

No dangerous reaction known under conditions of normal use.

10.4 CONDITIONS TO AVOID

Heat. Incompatible materials. Sources of ignition. Excessive water.

10.5 INCOMPATIBLE MATERIALS

Strong oxidizing agents. Strong reducing agents. Moisture.

10.6 HAZARDOUS DECOMPOSITION PRODUCTS

May include, and are not limited to: oxides of carbon, hydrocarbons.

Section 11: TOXICOLOGICAL INFORMATION

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS

Likely Routes of Exposure: Skin contact, eye contact, inhalation, and ingestion.

Symptoms related to physical/chemical/toxicological characteristics:

Eye: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of

the conjunctiva.

Skin: May cause skin irritation. Symptoms may include redness, drying,

defatting and cracking of the skin.

Ingestion: May be fatal if swallowed and enters airways. This product may be

aspirated into the lungs and cause chemical pneumonitis. May cause

stomach distress, nausea or vomiting.

Inhalation: May cause respiratory tract irritation.

Acute Toxicity:

Ingredient	IDLH	LC50	LD50
	T		0 1 7000 "
Distillates (petroleum),		Inhalation	Oral >5000 mg/kg, rat;
hydrotreated light	Not available.	>5.2 mg/L 4h, rat	Dermal >2000 mg/kg, rabbit
Solvent naphtha			
(petroleum), heavy		Inhalation	Oral >5000 mg/kg, rat;
aromatic	Not available.	>5.28 mg/L 4h, rat	Dermal >2000 mg/kg, rabbit
Distillates (petroleum),			
hydrotreated heavy		Inhalation	Oral >5000 mg/kg, rat;
naphthenic	Not available.	>5.0 mg/L 4h, rat	Dermal >5000 mg/kg, rabbit
			Oral 490 mg/kg, rat;
			Dermal >2500 mg/kg, rat;
Naphthalene	250 ppm	Not available.	Dermal >20 g/kg, rabbit
Dinonylphenol,			
ethoxylated, phosphated	Not available.	Not available.	Not available.

Calculated overall Chemical Acute Toxicity Values		
LC50 (inhalation) LD50 (oral)		LD50 (dermal)
Not available.	> 2000 mg/kg, rat	> 2000 mg/kg, rabbit



Ingredient	Chemical Listed as Carcinogen or Potential Carcinogen (NTP, IARC, OSHA, ACGIH, CP65)*
Distillates (petroleum), hydrotreated light	Not listed.
Solvent naphtha (petroleum), heavy aromatic	Not listed.
Distillates (petroleum), hydrotreated heavy naphthenic	Not listed.
Naphthalene	G-A4, I-2B, N-2, CP65
Dinonylphenol, ethoxylated, phosphated	Not listed.

^{*} See Section 15 for more information.

11.2 DELAYED, IMMEDIATE, AND CHRONIC EFFECTS OF SHORT- AND LONG-TERM EXPOSURE

Skin Corrosion/Irritation: Based on available data, the classification criteria are not met.

Serious Eye Damage/Irritation: Causes serious eye irritation.

Respiratory Sensitization:

Skin Sensitization:

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

STOT-Single Exposure:

Based on available data, the classification criteria are not met.

Chronic Health Effects:

Carcinogenicity: Possible carcinogen.

Germ Cell Mutagenicity: Based on available data, the classification criteria are not met.

Reproductive Toxicity:

Developmental: Based on available data, the classification criteria are not met.

Fertility: Based on available data, the classification criteria are not met.

STOT-Repeated Exposure: Based on available data, the classification criteria are not met.

Aspiration Hazard: May be fatal if swallowed and enters airways.

Other Information: Not available.

Section 12: ECOLOGICAL INFORMATION

12.1 ECOTOXICITY

Acute/Chronic Toxicity: May cause long-term adverse effects in the aquatic environment.

12.2 PERSISTENCE AND DEGRADABILITY

Not available.

12.3 BIOACCUMULATIVE POTENTIAL

Bioaccumulation: Not available.

12.4 MOBILITY IN SOIL

Not available.

12.5 OTHER ADVERSE EFFECTS

Not available.

Trade Name: PB Penetrating Catalyst (Bulk)

Revision date: 2017-12-13







Section 13: DISPOSAL CONSIDERATIONS

13.1 WASTE TREATMENT METHODS

Disposal Method: This material must be disposed of in accordance with all

local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized

wherever possible.

Other disposal recommendations: Handle empty containers with care because residual

vapours are flammable.

Section 14: TRANSPORT INFORMATION

14.1 UN NUMBER

DOT NOM-004-SCT2-1994

NA 1993 Not regulated.

14.2 UN PROPER SHIPPING NAME

DOT NOM-004-SCT2-1994

Combustible liquid, n.o.s. (Petroleum distillate)

Not applicable.

14.3 TRANSPORT HAZARD CLASS (ES)

DOT NOM-004-SCT2-1994

Not applicable.

14.4 PACKING GROUP

DOT NOM-004-SCT2-1994

III Not applicable.

14.5 ENVIRONMENTAL HAZARDS

Not available.

14.6 TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL 73/78 AND THE IBC CODE

Not available.

14.7 SPECIAL PRECAUTIONS FOR USER

Do not handle until all safety precautions have been read and understood.

Section 15: REGULATORY INFORMATION

15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/ LEGISLATIONS SPECIFIC FOR THE CHEMICAL

US: SDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Mexico: SDS prepared pursuant to NOM-018-STPS-2000.



SARA Title III				
Ingredient	Section 302 (EHS) TPQ (lbs.)	Section 304 EHS RQ (lbs.)	CERCLA RQ (lbs.)	Section 313
Distillates (petroleum),				
hydrotreated light	Not listed.	Not listed.	Not listed.	Not listed.
Solvent naphtha (petroleum),				
heavy aromatic	Not listed.	Not listed.	Not listed.	Not listed.
Distillates (petroleum), hydrotreated heavy				
naphthenic	Not listed.	Not listed.	Not listed.	Not listed.
Naphthalene	Not listed.	Not listed.	100	313
Dinonylphenol, ethoxylated,	NI-CP-CI	NI a CP a Ca al	NI-1P-1-1	NI-1 Patad
phosphated	Not listed.	Not listed.	Not listed.	Not listed.

State Regulations

California Proposition 65:

This product contains a chemical known to the State of California to cause cancer.

Global Inventories:

Ingredient	USA TSCA
Distillates (petroleum), hydrotreated light	Yes.
Solvent naphtha (petroleum), heavy aromatic	Yes.
Distillates (petroleum), hydrotreated heavy naphthenic	Yes.
Naphthalene	Yes.
Dinonylphenol, ethoxylated, phosphated	Yes.

NFPA-National Fire Protection Association:		
Health:	2	
Fire:	2	
Reactivity:	0	

HMIS-Hazardous Materials Identification System:		
Health: 2*		
Fire:	2	
Physical Hazard:	0	

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

CP65 California Proposition 65

OSHA (O) Occupational Safety and Health Administration.

ACGIH (G) American Conference of Governmental Industrial Hygienists.

A1 - Confirmed human carcinogen.

A2 - Suspected human carcinogen.

A3 - Animal carcinogen.

A4 - Not classifiable as a human carcinogen.


A5 - Not suspected as a human carcinogen.

IARC (I) International Agency for Research on Cancer.

1 - The agent (mixture) is carcinogenic to humans.

2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.







2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.

3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.

4 - The agent (mixture, exposure circumstance) is probably not carcinogenic tohumans.

NTP (N) National Toxicology Program.

1 - Known to be carcinogens.

2 - Reasonably anticipated to be carcinogens.

Section 16: OTHER INFORMATION

Date of Preparation: Feb. 3, 2016

Version: 1.0

Revision Date: Dec. 13, 2017

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

End of Safety Data Sheet

Page 10 of 10